

What is claimed is:

1 1. A laundry dryer having an entrance sealing assembly for a hinged door, the
2 laundry dryer comprising:

3 a door frame, said door frame being provided with a door glass;
4 a frame cover having a frame cover panel in which an entrance hole is formed for
5 receiving said door frame, the frame cover panel having an inner end surface;

6 a front support, coupled with said frame cover, for supporting a drum, the front
7 support having an inner end surface; and

8 a unified sealing member having first and second ends, disposed between said frame
9 cover and said front support, the second end of said unified sealing member providing for
10 contact with the door glass when the hinged door is closed.

1 2. The laundry dryer as claimed in claim 1, said unified sealing member
2 comprising:

3 a head portion, formed at the first end to be installed between the inner end surfaces
4 of the frame cover panel of said frame cover and the support cover panel of said front support,
5 for sealing a first gap between said frame cover and said front support; and

6 a tail portion, formed at the second end to protrude from the sealed first gap, for
7 sealing a second gap between the door glass and said frame cover by being brought into
8 contact with the door glass when the hinged door is closed.

1 3. The laundry dryer as claimed in claim 2, wherein the frame cover panel of
2 said frame cover has a hooked inner end for receiving said head portion.

1 4. The laundry dryer as claimed in claim 2, wherein said tail portion is
2 deformed over a predetermined length to establish a planar contact with the door glass when
3 the hinged door is closed.

1 5. The laundry dryer as claimed in claim 2, wherein the sealing of the second
2 gap seals a third gap between the door glass and said door frame.

1 6. The laundry dryer as claimed in claim 2, wherein the sealing of the second
2 gap seals a fourth gap between said door frame and said frame cover.

1 7. The laundry dryer as claimed in claim 2, wherein the sealing of the second
2 gap seals a fifth gap between said door frame and said front support.